



## Soilfloc® DC70

Dust Control Encrusting Additive

### Product Description:

Soilfloc® DC70 is a high quality, high purity water dispersion of vinyl acetate polymer developed for dust control as a spray water encrusting additive.

Soilfloc® DC70 is designed to control dust on dirt / gravel roads, construction projects, mining operations, dirt race tracks, as well as agricultural applications.

The recommended dosage will form a solid crust that will resist both rain, wind and truck tires. Soilfloc® DC70 will reduce costs associated with dust control over using general watering practices.

### Application Rates:

Soilfloc® DC70 is added to the application tank (water trucks or water wagons) at the rate of 0.04 lb. per gallon of water or a 0.5% solution. Three to four spray applications will form a solid crust.

\*\* rates may vary based on soil type (Typical coverage = 2600 gallon water truck covers 11,600 sq yards)

The pressure of a fire hose is sufficient for mixing Soilfloc® DC70 in the spray tank

### Physical / Chemical Properties:

Appearance	White Liquid
Ionic Character	Non-ionic
Molecular Weight	Very High
Approx. bulk density (g/cm <sup>3</sup> )	1.1
Bulk Viscosity (cps)	< 1000
Maximum Concentration (g/l)	10
Storage temperature (°F)	41°-86°
Shelf life (months)*	6

\* When stored inside a building at a stable temperature between 41° and 86° F



### Packaging Available:

5 gallon plastic pails	40 lb.
55 gallon plastic drums	441 lb.
275 gallon totes	2535 lb.

**Call for a product  
quotation today!  
Toll free 877-771-6041**

The information presented in this product bulletin is given in good faith and is true and accurate to the best of our knowledge. No warranty or guarantee is expressed or implied regarding the accuracy of such data. It is the user's responsibility to determine the suitability for his or her own use of the information presented.